





Note:
1. Distance from workshop backspin to crane peak should ≥200mm
2. Control mode: pendent control & remote control

Technical Parameters					
Crane Travelling			Electric Hoist		
Span (m)		0.39	Type		NR5t
Travelling Speed (m/min)		2.0~20	Lifting Speed (m/min)		0.8/5.0
Buffer Stroke (mm)		60	Lifting Height (m)		10
Max. Wheel Load (kN)		36.3	Lifting Motor	Type	NR
Rail Width (mm)		200~400		Power (kW)	4.9kW
Wheel Diameter (mm)		4*φ140	Travelling Speed (m/min)		1.0~10
Crane Travelling Motor	Type	SX050	Hoist Travelling Motor	Type	NR-0.45
	Power (kW)	2*0.4kW		Power (kW)	0.45kW
	Rotation Speed (r/min)	1415	Power Supply		
Crane Travelling Reducer		Type SX100			
		Ratio 7.7			

4		Electric system	Subassembly	1			
3		Hoist	Subassembly	1			
2		Girder	Subassembly	1			
1		End beam	Subassembly	2			
Part Number	Drawing number	Description	Material	Qty	Single Weight (kg)	Total	Remarks
Amended Mark	Qty	Zone	Amended file	Signature	Date	NLX single girder under hang crane NLX5t-0.39m A5	
Designed by			Standardized by				
Drawn by			Electrical Designer			General layout	
Checked by			Reviewed by				
Quality Assurance			Approved by			Project Title:	

Yuantai Crane Machinery

Sheet 1 of 1	Weight	Scale
Edition	2.78t	Not In Scale
Drawing Number: NLX5-0.39 A5		
Project Title:		